



## Drive Clean Synthetic Motor Oil

Drive Clean Synthetic Motor Oils are fully synthetic engine oils recommended for use in high- performance, turbocharged, supercharged, or naturally aspirated gasoline engines in passenger cars, light trucks, vans and sport utility vehicles.

Drive Clean Synthetic Motor Oil exceeds GF-5/SN oils in wear control, cleanliness, piston deposits, shear stability, oxidation control, and seal and emission systems compatibility.

Drive Clean Synthetic Motor Oil is formulated with state-of-the-art additive technology to offer ultimate engine protection and peak performance under all types of driving conditions. Meets and exceeds new car warranty requirements as defined by ILSAC GF-5 standards, the API Resource Conserving SN classification.

### APPLICATIONS

Drive Clean Synthetic Motor Oil is recommended for gasoline engines used in passenger cars, light trucks, sports-utility vehicles, powerboats, and additional applications calling for an API SN or previous API "S" category oil is recommended.

### FEATURES AND BENEFITS

- Excellent wear protection
- Highest established level of fuel economy
- Protection from varnish, deposits and sludge caused by stop-and-go driving
- Resistance to viscosity and high-temperature thermal breakdown
- Excellent low-temperature pumpability for reliable cold starts
- Extended drain intervals and complete Flex Fuel compatibility

### RECOMMENDED PERFORMANCE SPECIFICATIONS

Drive Clean Synthetic Motor Oil meets or exceeds the performance requirements of virtually all vehicles operating in North American including: Toyota, General Motors, Volkswagen, Ford, Hyundai, Honda, Nissan, BMW, Chrysler, Mazda, Mitsubishi, etc.

- ILSAC GF-5
- API Resource Conserving SN and all previous "S" categories
- Chrysler MS 6395
- Ford WSS-M2C945-A (SAE 5W-20), WSS-M2C9456-A (SAE 5W-30)
- GM 6094M and GM 4718M

PROPERTIES	DRIVE CLEAN SYNTHETIC MOTOR OIL
	SAE Viscosity Grade 0W-20
Gravity, °API	34
Flash Point, COC °C/°F	222/431
Pour Point, °C/°F	-38/-36
Viscosity, cSt @ 40 °C	38.0
Viscosity, cSt @ 100 °C	7.1
Viscosity Index	165
CCS Viscosity (mPa.s)	5500@-35°C
Noack Volatility (%wt)	<15

*Minor variations in test data are to be expected in normal manufacturing*

**Product Disclaimer** Valley Pacific Petroleum Services and its subsidiaries disclaim any warranties with respect to this product, the safety or suitability thereof, or the results to be obtained, whether express or implied, INCLUDING WITHOUT LIMITATION, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE AND/OR OTHER WARRANTY. Buyers and users assume all risk, responsibility and liability whatsoever from any and all injuries (including death), losses, or damages to persons or property arising from the use of this product. Under no circumstances shall Valley Pacific Petroleum Services or any of its subsidiaries be liable for special, consequential or incidental damages or for anticipated loss of profits.



## Drive Clean Synthetic Motor Oil

SDS# 1001 Version 1.0

Effective Date 01/09/2018

### SECTION 1. PRODUCT IDENTIFIER

<b>Product Name</b>	Drive Clean Synthetic Motor Oil (ILSAC GF-5/API SN)
<b>Product Grade</b>	SAE 0W-20
<b>Relevant Uses</b>	Passenger Car Engine Oil/ Gasoline Engine Oil
<b>Company Identification</b>	Valley Pacific Petroleum Services 152 Frank West Circle, Suite 100 Stockton, CA 95206-4098 1-800-266-3782 www.vpps.net
<b>Emergency Contact</b>	CHEMTREC: 1-800-424-9300 or 703-527-3887

### SECTION 2. HAZARDS IDENTIFICATION

<b>Classification (GHS-US)</b>	Aquatic Acute 2 H411 Full text of H-phrases: see section 16
<b>Label Elements</b>	GHS-US Labeling Hazard Pictograms (GHS-US)
<b>Signal Word</b>	none
<b>Hazard Statements (GHS-US)</b>	H411 - Toxic to aquatic life with long lasting effects.
<b>Precautionary Statements (GHS-US)</b>	<b>Prevention</b> P273: Avoid release into the environment.
<b>Other hazards</b>	<b>Response</b> P391: Collect Spillage  The mixture consists of substances capable of producing an aspiration hazard. Aspiration may result in chemical pneumonia (fluid in the lungs), severe lung damage, respiratory failure, and even death.  <b>Storage:</b> none <b>Disposal</b>
<b>Unknown Acute Toxicity (GHS-US)</b>	P501 - Dispose of contents/container in accordance with local, regional, national, and international regulations.  20.73 percent of the mixture consists of ingredients of unknown acute toxicity.



## Drive Clean Synthetic Motor Oil

SDS# 1001 Version 1.0

Effective Date 01/09/2018

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

**Substances** Not applicable

#### Mixture

Name	Product Identifier	% (w/w)	Classification (GHS-US)
heavy paraffinic, Distillates, petroleum, hydrotreated heavy paraffinic	(CAS No) 64742-54-7	45 – 51, 55 - 67	Asp. Tox. 1, H304
Paraffin oils*	(CAS No) 8012-95-1	0 - 0.1, 0.1- 1, 1 - 5	Asp. Tox. 1, H304 Aquatic Chronic 4, H413
1-Decene, homopolymer, hydrogenated	(CAS No) 68037-01-4	25 – 42, 20 - 30	Asp. Tox. 1, H304
Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts	(CAS No) 68649-42-3	2.7 - 11.75	Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Acute 2, H401 Aquatic Chronic 2, H411

\*The specific chemical identity and/or exact percentage of composition have been withheld as a trade secret within the meaning of the OSHA Hazard Communication Standard [29 CFR 1910.1200].

\*More than one of the ranges of concentration prescribed by Controlled Products Regulations has been used where necessary, due to varying composition.

Full text of H-phrases: see section 16

### SECTION 4. FIRST AID MEASURES

**Description of First Aid Measures** **General:** Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label if possible). **Inhalation:** Remove to fresh air and keep at rest in a position comfortable for breathing. Obtain medical attention if breathing difficulty persists.

**Skin Contact:** Remove contaminated clothing. Drench affected area with water or soap and water for at least 15 minutes. Wash contaminated clothing before reuse. Obtain medical attention if irritation develops or persists.

**Eye Contact:** Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention.

**Ingestion:** Do NOT induce vomiting. Rinse mouth. Immediately call a POISON CENTER or doctor/physician.

#### Most important symptoms and effects, both acute and delayed

**General:** No known significant effects or critical hazards.

**Inhalation:** Overexposure may be irritating to the respiratory system.

**Skin Contact:** Repeated or prolonged skin contact may cause irritation. **Eye Contact:** Direct contact with the eyes is likely irritating.

**Ingestion:** Ingestion is likely to be harmful or have adverse effects.

**Chronic Symptoms:** No known significant effects or critical hazards.



## Drive Clean Synthetic Motor Oil

SDS# 1001 Version 1.0

Effective Date 01/09/2018

### Indication of Any Immediate Medical Attention and Special Treatment Needed

If you feel unwell, seek medical advice (show the label where possible).

## SECTION 5. FIREFIGHTING MEASURES

<b>Suitable extinguishing media</b>	Use extinguishing media appropriate for surrounding fire.
<b>Unsuitable extinguishing media</b>	Do not use a heavy water stream. Use of heavy stream of water may spread fire.
<b>Fire Hazard</b>	Not flammable but will support combustion.
<b>Explosion Hazard</b>	Product is not explosive.
<b>Reactivity</b>	Hazardous reactions will not occur under normal conditions.
<b>Precautionary Measures Fire</b>	Exercise caution when fighting any chemical fire. Under fire conditions, hazardous fumes will be present.
<b>Firefighting Instructions</b>	Use water spray or fog for cooling exposed containers.
<b>Protection During Firefighting</b>	Do not enter fire area without proper protective equipment, including respiratory protection.
<b>Hazardous Combustion Products</b>	Under fire conditions, may produce fumes, smoke, oxides of carbon and hydrocarbons.
<b>Other Information</b>	Refer to Section 9 for flammability properties.
<b>Reference to Other Sections</b>	Refer to section 9 for flammability properties.

## SECTION 6. ACCIDENTAL RELEASE MEASURES

<b>Personal precautions, protective equipment and emergency procedures</b>	Avoid all contact with skin, eyes, or clothing. Avoid breathing (vapor, mist, spray).
<b>For Non-Emergency Personnel</b>	<b>Protective Equipment:</b> Use appropriate personal protection equipment (PPE). <b>Emergency Procedures:</b> Evacuate unnecessary personnel.
<b>For Emergency Personnel</b>	<b>Protective Equipment:</b> Equip cleanup crew with proper protection. <b>Emergency Procedures:</b> Stop leak if safe to do so. Eliminate ignition sources. Ventilate area.
<b>Environmental precautions</b>	Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.
<b>Methods and materials for containment and cleaning up</b>	<b>For Containment:</b> Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. <b>Methods for Cleaning Up:</b> Clean up spills immediately and dispose of waste safely. Spills should be contained with mechanical barriers. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill.



## Drive Clean Synthetic Motor Oil

SDS# 1001 Version 1.0

Effective Date 01/09/2018

**Reference to Other Sections** See Heading 8. Exposure controls and personal protection. For further information refer to section 13.

### SECTION 7. HANDLING AND STORAGE

**Precautions for Safe Handling** **Additional Hazards When Processed:** Any proposed use of this product in elevated-temperature processes should be thoroughly evaluated to assure that safe operating conditions are established and maintained. Practice good housekeeping - spillage can be slippery on smooth surface either wet or dry.

**Hygiene Measures:** Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

**Conditions for safe storage, including any incompatibilities**

**Technical Measures:** Comply with applicable regulations.

**Storage Conditions:** Store in a dry, cool and well-ventilated place. Keep container closed when not in use. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials.

**Incompatible Materials:** Strong acids, strong bases, strong oxidizers.

**Specific End Use(s)** Engine Oil

### SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

**Control Parameters** For substances listed in section 3 that are not listed here, there are no established Exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), NIOSH (REL), OSHA (PEL), Canadian provincial governments, or the Mexican government.

Paraffin oils (8012-95-1)		
USA ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup> (excluding metal working fluids, highly & severely refined-inhalable fraction)
USA ACGIH	ACGIH chemical category	Not Classifiable as a Human Carcinogen highly and severely refined, Suspected Human Carcinogen highly and severely refined
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup>
USA NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup>
USA NIOSH	NIOSH REL (STEL) (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
USA IDLH	US IDLH (mg/m <sup>3</sup> )	2500 mg/m <sup>3</sup>
Alberta	OEL STEL (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
Alberta	OEL TWA (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup>
British Columbia	OEL TWA (mg/m <sup>3</sup> )	0.2 mg/m <sup>3</sup> (mildly refined) 1 mg/m <sup>3</sup> (severely refined)
Manitoba	OEL TWA (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup> (excluding metal working fluids, highly & severely refined-inhalable fraction)
New Brunswick	OEL STEL (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>



## Drive Clean Synthetic Motor Oil

SDS# 1001 Version 1.0

Effective Date 01/09/2018

Paraffin oils (8012-95-1)		
New Brunswick	OEL TWA (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup> (as sampled by a method that does not collect vapor)
Newfoundland & Labrador	OEL TWA (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup> (excluding metal working fluids, highly & severely refined-inhalable fraction)
Nova Scotia	OEL TWA (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup> (excluding metal working fluids, highly & severely refined-inhalable fraction)
Nunavut	OEL STEL (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
Nunavut	OEL TWA (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup>
Northwest Territories	OEL STEL (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
Northwest Territories	OEL TWA (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup>
Ontario	OEL TWA (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup> (pure, highly and severely refined, excluding metal working fluids-inhalable)
Prince Edward Island	OEL TWA (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup> (excluding metal working fluids, highly & severely refined-inhalable fraction)
Québec	VECD (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (mist)
Québec	VEMP (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup> (mist)
Saskatchewan	OEL STEL (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
Saskatchewan	OEL TWA (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup>
Yukon	OEL STEL (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
Yukon	OEL TWA (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup>

**Appropriate Engineering Controls** Ensure adequate ventilation, especially in confined areas. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure all national/local regulations are observed.

**Personal Protective Equipment** Protective goggles. Gloves. Insufficient ventilation: wear respiratory protection.



**Materials for Protective Clothing** Chemically resistant materials and fabrics.

**Hand Protection** Wear chemically resistant protective gloves.

**Eye Protection** Chemical goggles or safety glasses.

**Skin and Body Protection** Wear suitable protective clothing.

**Respiratory Protection** Use a NIOSH-approved respirator or self-contained breathing apparatus whenever exposure may exceed established Occupational Exposure Limits.

**Environmental Exposure Controls** Do not allow the product to be released into the environment.

**Consumer Exposure Controls** Do not eat, drink or smoke during use.



## Drive Clean Synthetic Motor Oil

SDS# 1001 Version 1.0

Effective Date 01/09/2018

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Physical State</b>	Liquid
<b>Appearance</b>	Amber
<b>Odor</b>	Slight Hydrocarbon
<b>Odor Threshold</b>	Not available
<b>pH</b>	Not available
<b>Evaporation Rate</b>	Not available
<b>Melting Point</b>	Not available
<b>Boiling Point</b>	280 °C (536 °F)
<b>Flash Point</b>	205 °C (COC) (401 °F)
<b>Auto-ignition Temperature</b>	Not available
<b>Decomposition Temperature</b>	Not available
<b>Flammability (solid, gas)</b>	Not available
<b>Lower Flammable Limit</b>	Not available
<b>Upper Flammable Limit</b>	Not available
<b>Vapor Pressure</b>	Not available
<b>Relative Vapor Density at 20 °C</b>	Not available
<b>Relative Density</b>	Not available
<b>Specific Gravity</b>	0.85
<b>Solubility</b>	Negligible
<b>Partition Coefficient: N-Octanol/ Water</b>	Not available
<b>Viscosity</b>	Not available
<b>Viscosity, Kinematic</b>	50 mm <sup>2</sup> /s @ 40 °C
<b>Explosive Properties</b>	Product is not explosive
<b>Explosion Data – Sensitivity to Mechanical Impact</b>	Not expected to present an explosion hazard due to mechanical impact
<b>Explosion Data – Sensitivity to Static Discharge</b>	Not expected to present an explosion hazard due to static discharge



## Drive Clean Synthetic Motor Oil

SDS# 1001 Version 1.0

Effective Date 01/09/2018

### SECTION 10. STABILITY AND REACTIVITY

<b>Reactivity</b>	Hazardous reactions will not occur under normal conditions.
<b>Chemical Stability</b>	Stable under recommended handling and storage conditions (see section 7).
<b>Possibility of Hazardous Reactions</b>	Hazardous polymerization will not occur.
<b>Conditions to Avoid</b>	Direct sunlight, extremely high or low temperatures, heat, hot surfaces, sparks, open flames, incompatible materials, and other ignition sources.
<b>Incompatible Materials</b>	Strong acids, strong bases, strong oxidizers.
<b>Hazardous Decomposition Products</b>	Thermal decomposition generates : carbon oxides (CO, CO2). Hydrocarbons.

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Information on Toxicological Effects - Product

<b>Acute Toxicity</b>	Not classified
<b>LD50 and LC50 Data</b>	Not available
<b>Skin Corrosion/Irritation</b>	Not classified
<b>Eye Damage/Irritation</b>	Not classified
<b>Respiratory or Skin Sensitization</b>	Not classified
<b>Germ Cell Mutagenicity</b>	Not classified
<b>Teratogenicity</b>	Not classified
<b>Carcinogenicity</b>	Not classified
<b>Specific Target Organ Toxicity (Repeated Exposure)</b>	Not classified
<b>Reproductive Toxicity</b>	Not classified
<b>Specific Target Organ Toxicity (Single Exposure)</b>	Not classified
<b>Aspiration Hazard</b>	Not classified
<b>Symptoms/Injuries After Inhalation</b>	Overexposure may be irritating to the respiratory system.
<b>Symptoms/Injuries After Skin Contact</b>	Repeated or prolonged skin contact may cause irritation.





## Drive Clean Synthetic Motor Oil

SDS# 1001 Version 1.0

Effective Date 01/09/2018

<b>Symptoms/Injuries After Eye Contact</b>	Direct contact with the eyes is likely irritating.
<b>Symptoms/Injuries After Ingestion</b>	Ingestion is likely to be harmful or have adverse effects.
<b>Chronic Symptoms</b>	Not Classified

### INFORMATION ON TOXICOLOGICAL EFFECTS - INGREDIENT(S)

LD50 and LC50 Data:

<b>Paraffin oils (8012-95-1)</b>	
LC50 Inhalation Rat	2062 ppm/4h
ATE US (gases)	2,062.00 ppmV/4h
<b>Heavy paraffinic, Distillates, petroleum, hydrotreated heavy paraffinic (64742-54-7)</b>	
LD50 Oral Rat	> 2000 mg/kg
LD50 Dermal Rabbit	> 2 g/kg
<b>Petroleum distillates, solvent dewaxed (64742-65-0)</b>	
LD50 Oral Rat	> 5000 mg/kg
LD50 Dermal Rabbit	> 5 g/kg
<b>Paraffin oils (8012-95-1)</b>	
IARC Group	1

## SECTION 12. ECOLOGICAL INFORMATION

### TOXICITY

**Ecology - General** Toxic to aquatic life.

<b>Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts (68649-42-3)</b>	
LC50 Fish 1	1.0 - 5.0 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 1	1 - 1.5 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC 50 Fish 2	10.0 - 35.0 mg/l (Exposure time: 96 h - Species: Pimephales promelas [semi-static])
<b>Petroleum distillates, solvent dewaxed (64742-65-0)</b>	
EC50 Daphnia 1	> 1000 mg/L (Exposure time: 48 h - Species: Daphnia magna)
LC50 Fish 1	> 5000 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)
<b>Distillates, petroleum, hydrotreated heavy paraffinic (64742-54-7)</b>	
LC50 Fish 1	> 5000 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)
EC50 Daphnia 1	> 1000 mg/l (Exposure time: 48 h - Species: Daphnia magna)

**Persistence and Degradability** Not available

**Bioaccumulative Potential** Not available



## Drive Clean Synthetic Motor Oil

SDS# 1001 Version 1.0

Effective Date 01/09/2018

**Mobility in Soil** Not available

**Other Adverse Effects** Other Information: Avoid release to the environment.

### SECTION 13. DISPOSAL CONSIDERATIONS

**Waste treatment methods** **Sewage Disposal Recommendations:** Do not empty into drains; dispose of this material and its container in a safe way. Do not empty into drains. Do not dispose of waste into sewer.

**Waste Disposal Recommendations:** Dispose of waste material in accordance with all local, regional, national, provincial, territorial and international regulations.

### SECTION 14. TRANSPORT INFORMATION

**In Accordance with DOT** Not regulated for transport

**In Accordance with IMDG** Not regulated for transport

**In Accordance with IATA** Not regulated for transport

**In Accordance with TDG** Not regulated for transport

### SECTION 15. REGULATORY INFORMATION

#### US Federal Regulations

**SARA Section 311/312 Hazard Classes** Delayed (chronic) health hazard

#### US State Regulations

##### Paraffin oils (8012-95-1)

U.S. - California - Right To Know List – Warning: This material may contain chemicals known to the State of California to cause cancer, birth defects or other reproductive harm, and which may be subject to the warning requirements of California Proposition 65 (CA Health & Safety Code Section 25249.5)

U.S. - Massachusetts - Right to Know List

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Pennsylvania - RTK (Right to Know) List



## Drive Clean Synthetic Motor Oil

SDS# 1001 Version 1.0

Effective Date 01/09/2018

### Canadian Regulations

WHMIS Classification	Not Classified
<b>Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts (68649-42-3)</b>	
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Class D Division 2 Subdivision B - Toxic material causing other toxic effects
<b>Paraffin oils (8012-95-1)</b>	
Listed on the Canadian DSL (Domestic Substances List)	
Listed on the Canadian IDL (Ingredient Disclosure List)	
IDL Concentration 1 %	
WHMIS Classification	Class D Division 2 Subdivision A - Very toxic material causing other toxic effects
<b>Petroleum distillates, solvent dewaxed (64742-65-0)</b>	
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Uncontrolled product according to WHMIS classification criteria
<b>Distillates, petroleum, hydrotreated heavy paraffinic (64742-54-7)</b>	
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Uncontrolled product according to WHMIS classification criteria

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR

### SECTION 16. OTHER INFORMATION

#### Other Information

This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.



## Drive Clean Synthetic Motor Oil

SDS# 1001 Version 1.0

Effective Date 01/09/2018

### GHS Full Text Phrases

Aquatic Acute 2	Hazardous to the aquatic environment - Acute Hazard Category 2
Aquatic Chronic 2	Hazardous to the aquatic environment - Chronic Hazard Category 2
Aquatic Chronic 4	Hazardous to the aquatic environment - Chronic Hazard Category 4
Asp. Tox. 1	Aspiration hazard Category 1
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Skin Irrit. 2	Skin corrosion/irritation Category 2
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H318	Causes serious eye damage
H391	Collect Spillage
H401	Toxic to aquatic life
H411	Toxic to aquatic life with long lasting effects
H413	May cause long lasting harmful effects to aquatic life
H501	Dispose of contents/container in accordance with local, regional, national, and international regulations.

**Disclaimer** Valley Pacific Petroleum Services and its subsidiaries disclaim any warranties with respect to this product, the safety or suitability thereof, or the results to be obtained, whether express or implied, INCLUDING WITHOUT LIMITATION, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE AND/OR OTHER WARRANTY. Buyers and users assume all risk, responsibility and liability whatsoever from any and all injuries (including death), losses, or damages to persons or property arising from the use of this product. Under no circumstances shall Valley Pacific Petroleum Services or any of its subsidiaries be liable for special, consequential or incidental damages or for anticipated loss of profits.