



## Power THF

Power THF is a tractor hydraulic fluid formulated from premium base stocks and state-of-the-art additive technology. It is designed for use in a variety of farm equipment, off-highway machinery, industrial tractors, final drives, power take-off units, wet brakes, power steering units and hydraulic systems.

Power THF is made with special friction modifiers combined with extremely shear-stable viscosity modifiers offer a supreme performance level. This new and improved fluid offers the convenience of using one tractor fluid in place of two or more fluids while maintaining optimum component performance and durability.

### APPLICATIONS

Power THF is suitable for use in all major OEM equipment including but not limited to Kubota, Oliver, Minneapolis-Moline, International Harvester, White Farm, John Deere, Deutz-Allis Chalmers, Ford-New Holland, J.I. Case and Massey Ferguson.

Power THF is recommended against the following:

- John Deere- Quatrol, J20A, J20C, J21A, Hy-Gard J14B/C, Type 303
- International Harvester- Hy-Tran, B-6
- Massey Ferguson- M-1110, M-1127B, M-1129A, M-1135, M-1141
- Allis Chalmers- Power Fluid 821 XL
- J.I. Case- TFD (JIC-143/146), Hi-Vis (JIC-185), JIC-144/145, MS-1204, MS1205/1206/1207, MS-1210 (TCH) and B-6
- Ford New Holland- M2C86-A/B/C, M2C134-A/B/C/D, M2C41-B, M2C43, M2C53-A/B, M2C92-A
- Vickers- I-2986-S
- Kubota Universal Transdraulic Fluid- UTD

### FEATURES AND BENEFITS

- Superior wear protection
- Excellent rust and corrosion protection
- Protection against varnish and sludge formation
- Superior thermal stability and oxidation resistance
- Outstanding low-temperature

POWER THF	TYPICAL CHARACTERISTICS
API Gravity @ 60° C	30.3
Lbs. / gallon	7.2
Viscosity, cPs @ 100°C	9.6
Viscosity, cPs @ 40°C	54.4
Viscosity Index	119
Flash Point, C°	218
Pour Point, C°	-35

**Product Disclaimer** Valley Pacific Petroleum Services and its subsidiaries disclaim any warranties with respect to this product, the safety or suitability thereof, or the results to be obtained, whether express or implied, INCLUDING WITHOUT LIMITATION, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE AND/OR OTHER WARRANTY. Buyers and users assume all risk, responsibility and liability whatsoever from any and all injuries (including death), losses, or damages to persons or property arising from the use of this product. Under no circumstances shall Valley Pacific Petroleum Services or any of its subsidiaries be liable for special, consequential or incidental damages or for anticipated loss of profits.

**Power THF**

SDS# 1010, Version 1.0

Issue Date 01/15/2018

**SECTION 1. PRODUCT IDENTIFIER**

<b>Product Name</b>	Power THF
<b>Product Grades</b>	Not applicable
<b>Relevant Uses</b>	Tractor Hydraulic Fluid/Hydraulic Fluid
<b>Company Identification</b>	Valley Pacific - Headquarters 152 Frank West Circle, Suite 100 Stockton, CA 95206-4098 1-800-266-3782 www.vpps.net
<b>Emergency Contact</b>	CHEMTREC: 1- 800-424-9300 or 703-527-3887

**SECTION 2. HAZARDS IDENTIFICATION**

<b>Classification of the Substance or Mixture</b>	Classification (GHS-US) Not Classified Full text of H-phrases: see section 16
<b>Label Elements</b>	
<b>GHS-US Labeling</b>	
<b>Hazard Pictograms (GHS-US)</b>	None Required
<b>Signal Word (GHS-US)</b>	Not Hazardous
<b>Hazard Statements (GHS-US)</b>	None Required
<b>Precautionary Statements (GHS-US)</b>	P273 - Avoid release to the environment. P501 - Dispose of contents/container in accordance with local, regional, national, and international regulations.
<b>Other Hazards</b>	The mixture consists of substances capable of producing an aspiration hazard. Aspiration may result in chemical pneumonia (fluid in the lungs), severe lung damage, respiratory failure, and even death.
<b>Unknown Acute Toxicity (GHS-US)</b>	9.73 percent of the mixture consists of ingredient(s) of unknown acute toxicity.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

<b>Substances</b>	Not applicable
-------------------	----------------

**Power THF**

SDS# 1010, Version 1.0

Issue Date 01/15/2018

**Mixture**

Name	Product Identifier	% (w/w)	Classification (GHS-US)
Petroleum distillates, solvent dewaxed	(CAS No) 64742-65-0	75.75 –95, 64 - 85	Not Classified
heavy paraffinic, Distillates, petroleum, hydrotreated heavy paraffinic	(CAS No) 64742-54-7	0 – 11,10 - 17	Not Classified
Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts	(CAS No) 68649-42-3	0.7 -2.7	Aquatic Chronic 3, H402

\*The specific chemical identity and/or exact percentage of composition have been withheld as a trade secret within the meaning of the OSHA Hazard Communication Standard [29 CFR 1910.1200].

\*More than one of the ranges of concentration prescribed by Controlled Products Regulations has been used where necessary, due to varying composition.

Full text of H-phrases: see section 16

**SECTION 4. FIRST AID MEASURES**

<b>General</b>	Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label if possible).
<b>Inhalation</b>	Remove to fresh air and keep at rest in a position comfortable for breathing. Obtain medical attention if breathing difficulty persists.
<b>Skin Contact</b>	Remove contaminated clothing. Drench affected area with water or soap and water for at least 15 minutes. Wash contaminated clothing before reuse. Obtain medical attention if irritation develops or persists.
<b>Eye Contact</b>	Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention.
<b>Ingestion</b>	Do NOT induce vomiting. Rinse mouth. Immediately call a POISON CENTER or doctor/physician.

**Most Important Symptoms and Effects Both Acute and Delayed**

<b>General</b>	No known significant effects or critical hazards.
<b>Inhalation</b>	Overexposure may be irritating to the respiratory system. Skin Contact: Repeated or prolonged skin contact may cause irritation.
<b>Eye Contact</b>	Direct contact with the eyes is likely irritating.
<b>Ingestion</b>	Ingestion is likely to be harmful or have adverse effects.
<b>Chronic Symptoms</b>	No known significant effects or critical hazards.
<b>Indication of Any Immediate Medical Attention and Special Treatment Needed</b>	If you feel unwell, seek medical advice (show the label where possible).

**Power THF**

SDS# 1010, Version 1.0

Issue Date 01/15/2018

**SECTION 5. FIREFIGHTING MEASURES**

<b>Suitable Extinguishing Media</b>	Use extinguishing media appropriate for surrounding fire.
<b>Unsuitable Extinguishing Media</b>	Do not use a heavy water stream. Use of heavy stream of water may spread fire.
<b>Fire Hazard</b>	Not flammable but will support combustion.
<b>Explosion Hazard</b>	Product is not explosive.
<b>Reactivity</b>	Hazardous reactions will not occur under normal conditions.
<b>Advice for Firefighters</b>	
<b>Precautionary Measures Fire</b>	Exercise caution when fighting any chemical fire. Under fire conditions, hazardous fumes will be present.
<b>Firefighting Instructions</b>	Use water spray or fog for cooling exposed containers.
<b>Protection During Firefighting</b>	Do not enter fire area without proper protective equipment, including respiratory protection.
<b>Hazardous Combustion Products</b>	Under fire conditions, may produce fumes, smoke, oxides of carbon and hydrocarbons.
<b>Other Information</b>	Refer to Section 9 for flammability properties.
<b>Reference to Other Sections</b>	Refer to section 9 for flammability properties.

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

<b>Personal Precautions, Protective Equipment and Emergency Procedures</b>	<b>General Measures:</b> Avoid all contact with skin, eyes, or clothing. Avoid breathing (vapor, mist, spray).
<b>For Non-Emergency Personnel</b>	
<b>Protective Equipment</b>	Use appropriate personal protection equipment (PPE).
<b>Emergency Procedures</b>	Evacuate unnecessary personnel.
<b>For Emergency Personnel</b>	
<b>Protective Equipment</b>	Equip cleanup crew with proper protection.
<b>Emergency Procedures</b>	Stop leak if safe to do so. Eliminate ignition sources. Ventilate area.
<b>Environmental Precautions</b>	Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.
<b>Methods and Material for Containment and Cleaning Up</b>	<b>For Containment:</b> Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

**Power THF**

SDS# 1010, Version 1.0

Issue Date 01/15/2018

**Methods for Cleaning Up**

Clean up spills immediately and dispose of waste safely. Spills should be contained with mechanical barriers. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill.

**Reference to Other Sections**

See Heading 8. Exposure controls and personal protection. For further information refer to section 13.

**SECTION 7. HANDLING AND STORAGE****Precautions for Safe Handling****Additional Hazards When Processed**

Any proposed use of this product in elevated-temperature processes should be thoroughly evaluated to assure that safe operating conditions are established and maintained. Practice good housekeeping - spillage can be slippery on smooth surface either wet or dry.

**Hygiene Measures**

Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

**Conditions for Safe Storage, Including Any Incompatibilities****Technical Measures**

Comply with applicable regulations.

**Storage Conditions**

Store in a dry, cool and well-ventilated place. Keep container closed when not in use. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials.

**Incompatible Materials**

Strong acids, strong bases, strong oxidizers.

**Specific End Use(s)**

Hydraulic Fluid.

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION****Control Parameters**

For substances listed in section 3 that are not listed here, there are no established Exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), NIOSH (REL), OSHA (PEL), Canadian provincial governments, or the Mexican government.

**Exposure Controls**

**Appropriate Engineering Controls:** Ensure adequate ventilation, especially in confined areas. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure all national/local regulations are observed.

**Personal Protective Equipment**

Protective goggles. Gloves.



**Power THF**

SDS# 1010, Version 1.0

Issue Date 01/15/2018

<b>Insufficient ventilation</b>	Wear respiratory protection.
<b>Materials for Protective Clothing</b>	Chemically resistant materials and fabrics.
<b>Hand Protection</b>	Wear chemically resistant protective gloves.
<b>Eye Protection</b>	Chemical goggles or safety glasses.
<b>Skin and Body Protection</b>	Wear suitable protective clothing.
<b>Respiratory Protection</b>	Use a NIOSH-approved respirator or self-contained breathing apparatus whenever exposure may exceed established Occupational Exposure Limits.
<b>Environmental Exposure Controls</b>	Do not allow the product to be released into the environment.
<b>Consumer Exposure Controls</b>	Do not eat, drink or smoke during use.

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

<b>Physical State</b>	Liquid
<b>Appearance</b>	Amber
<b>Odor</b>	Slight Hydrocarbon
<b>Odor Threshold</b>	Not available
<b>pH</b>	Not available
<b>Evaporation Rate</b>	Not available
<b>Melting Point</b>	Not available
<b>Boiling Point</b>	Not available
<b>Flash Point</b>	>204°C / >400°F
<b>Auto-ignition Temperature</b>	Not available
<b>Decomposition Temperature</b>	Not available
<b>Flammability (solid, gas)</b>	Not available
<b>Lower Flammable Limit</b>	Not available
<b>Upper Flammable Limit</b>	Not available
<b>Vapor Pressure</b>	Not available
<b>Relative Vapor Density at 20 °C</b>	Not available
<b>Relative Density</b>	Not available

**Power THF**

SDS# 1010, Version 1.0

Issue Date 01/15/2018

<b>Specific Gravity</b>	0.85
<b>Solubility</b>	Negligible
<b>Partition Coefficient: N-Octanol/ Water</b>	Not available
<b>Viscosity</b>	Not available
<b>Viscosity, Kinematic</b>	Not available
<b>Explosive Properties</b>	Product is not explosive
<b>Explosion Data – Sensitivity to Mechanical Impact</b>	Not expected to present an explosion hazard due to mechanical impact
<b>Explosion Data – Sensitivity to Static Discharge</b>	Not expected to present an explosion hazard due to static discharge

**SECTION 10. STABILITY AND REACTIVITY**

<b>Reactivity</b>	Hazardous reactions will not occur under normal conditions.
<b>Chemical Stability</b>	Stable under recommended handling and storage conditions (see section 7).
<b>Possibility of Hazardous Reactions</b>	Hazardous polymerization will not occur.
<b>Conditions to Avoid</b>	Direct sunlight, extremely high or low temperatures, heat, hot surfaces, sparks, open flames, incompatible materials, and other ignition sources.
<b>Incompatible Materials</b>	Strong acids, strong bases, strong oxidizers.
<b>Hazardous Decomposition Products</b>	No decomposition expected under normal use and storage conditions.

**SECTION 11. TOXICOLOGICAL INFORMATION****Information on Toxicological Effects - Product**

<b>Acute Toxicity</b>	Not classified
<b>LD50 and LC50 Data</b>	Not available
<b>Skin Corrosion/Irritation</b>	Not classified
<b>Eye Damage/Irritation</b>	Not classified
<b>Respiratory or Skin Sensitization</b>	Not classified
<b>Germ Cell Mutagenicity</b>	Not classified
<b>Teratogenicity</b>	Not classified



**Power THF**

SDS# 1010, Version 1.0

Issue Date 01/15/2018

<b>Carcinogenicity</b>	Not classified
<b>Specific Target Organ Toxicity (Repeated Exposure)</b>	Not classified
<b>Reproductive Toxicity</b>	Not classified
<b>Specific Target Organ Toxicity (Single Exposure)</b>	Not classified
<b>Aspiration Hazard</b>	Not classified
<b>Symptoms/Injuries After Inhalation</b>	Overexposure may be irritating to the respiratory system.
<b>Symptoms/Injuries After Skin Contact</b>	Repeated or prolonged skin contact may cause irritation.
<b>Symptoms/Injuries After Eye Contact</b>	Direct contact with the eyes is likely irritating.
<b>Symptoms/Injuries After Ingestion</b>	Ingestion is likely to be harmful or have adverse gastrointestinal effects.
<b>Chronic Symptoms</b>	Not classified

**Information on Toxicological Effects - Ingredient(s)**

**LD50 and LC50 Data:**

<b>Heavy paraffinic, Distillates, petroleum, hydrotreated heavy paraffinic (64742-54-7)</b>	
<b>LD50 Oral Rat</b>	> 2000 mg/kg
<b>LD50 Dermal Rabbit</b>	> 2 g/kg
<b>Petroleum distillates, solvent dewaxed (64742-65-0)</b>	
<b>LD50 Oral Rat</b>	> 5000 mg/kg
<b>LD50 Dermal Rabbit</b>	> 5 g/kg

**SECTION 12. ECOLOGICAL INFORMATION**

**Toxicity**

**Ecology - General** Toxic to aquatic life.

<b>Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts (68649-42-3)</b>	
<b>LC50 Fish 1</b>	1.0 - 5.0 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
<b>EC50 Daphnia 1</b>	1 - 1.5 mg/l (Exposure time: 48 h - Species: Daphnia magna)
<b>LC 50 Fish 2</b>	10.0 - 35.0 mg/l (Exposure time: 96 h - Species: Pimephales promelas [semi-static])
<b>Petroleum distillates, solvent dewaxed (64742-65-0)</b>	
<b>EC50 Daphnia 1</b>	> 1000 mg/L (Exposure time: 48 h - Species: Daphnia magna)





## Power THF

SDS# 1010, Version 1.0

Issue Date 01/15/2018

LC50 Fish 1	> 5000 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)
Distillates, petroleum, hydrotreated heavy paraffinic (64742-54-7)	
LC50 Fish 1	> 5000 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)
EC50 Daphnia 1	> 1000 mg/l (Exposure time: 48 h - Species: Daphnia magna)

<b>Persistence and Degradability</b>	Not available
<b>Bioaccumulative Potential</b>	Not available
<b>Mobility in Soil</b>	Not available
<b>Other Information</b>	Avoid release to the environment.

### SECTION 13. DISPOSAL CONSIDERATIONS

<b>Sewage Disposal Recommendations</b>	Do not empty into drains; dispose of this material and its container in a safe way.
	Do not empty into drains. Do not dispose of waste into sewer.
<b>Waste Disposal Recommendations</b>	Dispose of waste material in accordance with all local, regional, national, provincial, territorial and international regulations.

### SECTION 14. TRANSPORT INFORMATION

<b>In Accordance with DOT</b>	Not regulated for transport
<b>In Accordance with IMDG</b>	Not regulated for transport
<b>In Accordance with IATA</b>	Not regulated for transport
<b>In Accordance with TDG</b>	Not regulated for transport

### SECTION 15. REGULATORY INFORMATION

<b>US Federal Regulations</b>	SARA Section 311/312
<b>Hazard Classes</b>	Not Classified
<b>US State Regulations</b>	None noted

#### Canadian Regulations

WHMIS Classification	Not Classified
<b>Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts (68649-42-3)</b>	
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Class D Division 2 Subdivision B - Toxic material causing other toxic effects
<b>Petroleum distillates, solvent dewaxed (64742-65-0)</b>	
Listed on the Canadian DSL (Domestic Substances List)	



## Power THF

SDS# 1010, Version 1.0

Issue Date 01/15/2018

WHMIS Classification	Uncontrolled product according to WHMIS classification criteria
<b>Distillates, petroleum, hydrotreated heavy paraffinic (64742-54-7)</b>	
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Uncontrolled product according to WHMIS classification criteria

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR.

### SECTION 16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

**Other Information** This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

**GHS Full Text Phrases** P273 Avoid release into the environment  
P501 Dispose of contents/container in accordance with local, regional, national, and international regulations.

**Disclaimer** Valley Pacific Petroleum Services and its subsidiaries disclaim any warranties with respect to this product, the safety or suitability thereof, or the results to be obtained, whether express or implied, INCLUDING WITHOUT LIMITATION, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE AND/OR OTHER WARRANTY. Buyers and users assume all risk, responsibility and liability whatsoever from any and all injuries (including death), losses, or damages to persons or property arising from the use of this product. Under no circumstances shall Valley Pacific Petroleum Services or any of its subsidiaries be liable for special, consequential or incidental damages or for anticipated loss of profits.